



GAMMA series

Supply voltage selectable via power modules

2 change-over contacts

Width 22.5mm

Industrial design



Technical data

1. Functions

S Star-Delta start-up

2. Time ranges

Start-up time

Time range	Adjustment range
10s	500ms 10s
30s	1500ms 30s
1min	3s 1min
3min	9s 3min

Transit time

Time range (fixed)
40ms
60ms
80ms
100ms

3. Indicators

Green LED ON: indication of supply voltage delta-contactor in on-position (terminals 25-28)
 Green LED flashes: indication of star-time
 Yellow LED ON/OFF: indication of star-contactor (terminals 15-18)

4. Mechanical design

Self-extinguishing plastic housing, IP rating IP40
 Mounted on DIN-Rail TS 35 according to EN 50022
 Mounting position: any
 Shockproof terminal connection according to VBG 4 (PZ1 required), IP rating IP20
 Tightening torque: max. 1Nm
 Terminal capacity:
 1 x 0.5 to 2.5mm² with/without multicore cable end
 1 x 4mm² without multicore cable end
 2 x 0.5 to 1.5mm² with/without multicore cable end
 2 x 2.5mm² flexible without multicore cable end

5. Input circuit

Supply voltage: 12 to 400V AC terminals A1-A2 (galvanically separated) selectable via power modules TR2 according to specification of power module
 Tolerance: according to specification of power module
 Rated frequency: according to specification of power module
 Rated consumption: 2VA (1.5W)
 Duration of operation: 100%
 Reset time: 100ms
 Residual ripple for DC: -
 Drop-out voltage: >30% of the supply voltage
 Overvoltage category: III (in accordance with IEC 60664-1)
 Rated surge voltage: 4kV

6. Output circuit

2 potential free change-over contacts
 Rated voltage: 250V AC
 Switching capacity: 750VA (3A / 250V AC)
 If the distance between the devices is less than 5mm!

Switching capacity: 1250VA (5A / 250V AC)
 If the distance between the devices is greater than 5mm!

Fusing: 5A fast acting
 Mechanical life: 20 x 10⁶ operations
 Electrical Life: 2 x 10⁵ operations at 1000VA resistive load
 Switching frequency: max. 60/min at 100VA resistive load
 max. 6/min at 1000VA resistive load (in accordance with IEC 60947-5-1)
 Overvoltage category: III (in accordance with IEC 60664-1)
 Rated surge voltage: 4kV

7. Accuracy

Base accuracy: ±1% (of maximum scale value)
 Frequency response: -
 Adjustment accuracy: ≤5% (of maximum scale value)
 Repetition accuracy: <0.5% or ±5ms
 Voltage influence: -
 Temperature influence: ≤0.01% / °C


8. Ambient conditions

Ambient temperature: -25 to +55°C (in accordance with IEC 60068-1)
 -25 to +40°C (in accordance with UL 508)
 Storage temperature: -25 to +70°C
 Transport temperature: -25 to +70°C
 Relative humidity: 15% to 85% (in accordance with IEC 60721-3-3 class 3K3)
 Pollution degree: 3 (in accordance with IEC 60664-1)
 Vibration resistance: 10 to 55Hz 0.35mm (in accordance with IEC 60068-2-6)
 Shock resistance: 15g 11ms (in accordance with IEC 60068-2-27)


Functions

Star-Delta start-up (S)

When the supply voltage U is applied, the star-contact switches into on-position (yellow LED illuminated) and the set star-time t_1 begins (green LED flashing). After the interval t_1 has expired (green LED illuminated) the star-contact switches into off-position (yellow LED not illuminated) and the set transit-time t_2 begins. After the interval t_2 has expired the delta-contact switches into on-position. To restart the function the supply voltage must be interrupted and re-applied.



Connections



Dimensions

