



SPECIFIC N°: OD056A2Q2305Q4

MOTOR PART NR	OD056A2Q2305Q4	CUSTOMER PART NR	-	
DRAWING NR	OD056A2Q2305Q4	MOTOR TYPE	OD056A22305Q4	
Type of winding	3 PHASE 1 SPEED			
PROTECTION	II 2GD Ex d IIC T4 Gb Ex tb IIIC T125°C	CERTIFICATE	EUM1 10 ATEX 0350	
IP PROTECTION	IP66	ENVIRONMENT CONDITIONS	-40 /+50°C Max Altitude: 1000m	
POLES	2	NOMINAL POWER kW	0.09 0.11	
Nom. Speed rpm	2810 3370	Voltage-Frequency	230/400V 50Hz 265/460V 60Hz	Tolerance: Voltage ±5%
Nom. Current A	0.69/0.4 0.69/0.4	COS φ	0.75 0.75	
Duty	S1 Continuous Duty	Direction of Rotation	BIDIRECTIONAL	
Insulation Class	F	Mounting IM	B14	
IEC Frame Size	56	Material end Shield/Flange	Aluminium	
Material Terminal Box	Aluminium	Material Fan	Aluminium	
Material Cover Fan	Zinc plated steel	Material shaft	Steel C43	
DE Bearing Type	6202-ZZ	NDE Bearing Type	6202-ZZ	
Position of terminal box	TOP	Cable gland Type	N.1 M20x1,5	
Cable gland position (view from DE)	Right	Thermal protection	-	
Painting	-	Motor Colour	Not painted motor	
Run capacitor μF	-	Start capacitor	-	

In compliance with the EC Directives
 94/9/EC (ATEX)
 2004/108/EC (EMC)
 2006/42/EC (Machinery)
 2011/65/CE (RoHS)

and comply with the following Standards
 EN 60079-0, 1, 31
 EN 60034-1,2,5,6,7,9,12,14,
 IEC60072-1,
 EN 60259

Overall dimensions