



SPECIFIC N°: OD080A4F2305P4

MOTOR PART NR	OD080A4F2305P4	CUSTOMER PART NR	-
DRAWING NR	OD080A4F2305P4	MOTOR TYPE	OD080A42305P4
Type of winding	3 PHASE 1 SPEED		
PROTECTION	II 2G Ex d IIC T54 Gb	CERTIFICATE	EUM1 10 ATEX 0350
IP PROTECTION	IP66	ENVIRONMENT CONDITIONS	-20 /+50°C Max Altitude: 1000m
POLES	4	NOMINAL POWER kW	0.55 0.66
Nom. Speed rpm	1390 1670	Voltage-Frequency	230/400V 50Hz 265/460V 60Hz
Nom. Current A	3/1.75 3/1.75	COS $\phi$	0,71 0,71
Duty	S1 Continuous Duty	Direction of Rotation	BIDIRECTIONAL
Insulation Class	F	Mounting IM	B5
IEC Frame Size	80	Material end Shield/Flange	Aluminium
Material Terminal Box	Aluminium	Material Fan	Plastic nylon V6
Material Cover Fan	Zinc plated steel	Material shaft	Steel C43
DE Bearing Type	6204-ZZ	NDE Bearing Type	6204-ZZ
Position of terminal box	TOP	Cable gland Type	N.1 M20x1,5
Cable gland position (view from DE)	Right	Thermal protection	-
Painting	-	Motor Colour	Not painted motor
Run capacitor $\mu$ F	-	Start capacitor	-

*In compliance with the EC Directives*  
 94/9/EC (ATEX)  
 2004/108/EC (EMC)  
 2006/42/EC (Machinery)  
 2011/65/CE (RoHS)

*and comply with the following Standards*  
 EN 60079-0,  
 EN 60079-1,  
 EN 60034-1,2,5,6,7,9,12,14,  
 IEC60072-1,  
 EN 60259

**Overall dimensions**