

SPECIFIC N° OD132M4Q4005P4

MOTOR PART NR	OD132M4Q4005P4	CUSTOMER PART NR	-
DRAWING NR	OD132M4Q4005P4	MOTOR TYPE	OD132M44005P4
Type of winding	3 PHASE 1 SPEED		
PROTECTION	II 2G Ex d IIC T4 Gb	CERTIFICATE	EUM1 10 ATEX 0350
IP PROTECTION	IP66	ENVIRONMENT CONDITIONS	-20 /+50°C Max Altitude: 1000m
POLES	4	NOMINAL POWER kW	7.5
Nom. Speed rpm	1450	Voltage-Frequency	400/690V 50Hz Tolerance: Voltage $\pm 5\%$
Nom. Current A	15.6/9	COS ϕ	0.82
Duty	S1 Continuous Duty	Direction of Rotation	BIDIRECTIONAL
Insulation Class	F	Mounting IM	B14
IEC Frame Size	132L	Material end Shield/Flange	Aluminium
Material Terminal Box	Aluminium	Material Fan	Plastic V6
Material Cover Fan	Zinc plated steel	Material shaft	Steel C43
DE Bearing Type	6308-ZZ	NDE Bearing Type	6308-ZZ
Position of terminal box	TOP	Cable gland Type	N.2 M25
Cable gland position (view from DE)	Right	Thermal protection	-
Painting	-	Motor Colour	Not painted motor
Run capacitor μF	-	Start capacitor	-

In compliance with the EC Directives

94/9/EC (ATEX)
 2004/108/EC (EMC)
 2006/42/EC (Machinery)
 2011/65/CE (RoHS)

and comply with the following Standards

EN 60079-0, 1
 EN 60034-1,2,5,6,7,9,12,14,
 IEC60072-1,
 EN 60259

Overall dimensions
